







### Phillips Pan Head

Size	Point	Recommendations	Picture (Not to a particular size)
6-20 x 3/8 6-20 x 1/2 6-20 x 5/8 6-20 x 3/4 6-20 x 1	2	Recommended Drive Speed 2500 RPM. Attaches metal to metal. 20 to 18 gauge or thinner. 0.035 - 0.090	
8-18 x 3/8 8-18 x 1/2* 8-18 x 5/8 8-18 x 3/4* 8-18 x 1 8-18 x 1-1/4 8-18 x 1-1/2 8-18 x 2	2	Recommended Drive Speed 2500 RPM. Attaches metal to metal. 22 to 15 gauge or thinner. 0.035 - 0.100	
10-16 x 1/2 10-16 x 5/8 10-16 x 3/4* 10-16 x 1 10-16 x 1-1/4 10-16 x 1-1/2 10-16 x 2 10-16 x 3	2-3	Recommended Drive Speed 2250 RPM. Attaches metal to metal. 24 to 12 gauge or thinner. 0.035 - 0.100 #2 pt 0.035 - 0.176 #3 pt	


### 410 Stainless Steel Pan HD

Size	Point	Recommendations	Picture (Not to a particular size)
6-20 x 3/8 6-20 x 1/2	2	Recommended drive speed 2500 RPM. Attaches metal to metal. 20 to 18 gauge or thinner. 0.035 - 0.090	
8-18 x 1/2 8-18 x 5/8 8-18 x 3/4 8-18 x 1 8-18 x 1-1/4 8-18 x 1-1/2	2	Recommended drive speed 2500 RPM. Attaches metal to metal. 22 to 15 gauge or thinner. 0.035 - 0.100	
10-16 x 1/2 10-16 x 3/4 10-16 x 1	2-3	Recommended drive speed 2250 RPM. Attaches metal to metal. 24 to 12 gauge or thinner. 0.035 - 0.100 #2 pt 0.035 - 0.176 #3 pt	



Knoxville Bolt and Screw, Inc.  
 Phone 865-573-1991  
 Fax 865-573-8617

[www.knoxvillebolt.com](http://www.knoxvillebolt.com)  
 800-231-3309  
 800-231-9566




### Pan HD Framing

Size	Point	Recommendations	Picture (Not to a particular size)
6-20 x 7/16 7-20 x 7-16	2	Attaches Metal track to metal studs 14 - 20 gauge.	


### Flat Head

Size	Point	Recommendations	Picture (Not to a particular size)
8-18 x 1/2 8-18 x 3/4 8-18 x 1 8-18 x 1-1/4 8-18 x 1-1/2	2	Recommended Drive Speed 2500 RPM. For counter-sunk holes. Aluminum to aluminum or steel to steel. 0.035 - 0.100	
10-16 x 3/4 10-16 x 1 10-16 x 1-1/2	3	For counter-sunk holes. Aluminum to aluminum or steel to steel. 0.035 - 0.176	


### 410 Stainless Steel Flat HD

Size	Point	Recommendations	Picture (Not to a particular size)
6-20 x 3/4 6-20 x 1	2	Recommended drive speed 2500 RPM. Attaches metal to metal. 20 to 18 gauge or thinner. 0.035 - 0.090	
8-18 x 3/4 8-18 x 1 8-18 x 1-1/2	2	Recommended drive speed 2500 RPM. For counter-sunk holes. Attaches aluminum to aluminum or steel to steel. 0.035 - 0.100	
10-16 x 3/4 10-16 x 1 10-16 x 1-1/2	3	Recommended drive speed 2250 RPM. For counter-sunk holes. Attaches aluminum to aluminum or steel to steel. 0.035 - 0.176	


### Flat HD w/Wings (Reamer)

Size	Point	Recommendations	Picture (Not to a particular size)
10-16 x 1-5/8 12-24 x 2 12-24 x 2-1/4 12-24 x 2-1/2 1/4-20 x 2-3/4 1/4-20 x 3-1/4 1/4-20 x 3-1/2 1/4-20 x 3-3/4	3-4	Attaches lumber to headers or 1/4 steel	


### Wafer HD

Size	Point	Recommendations	Picture (Not to a particular size)
8-18 x 1 10-24 x 3/4 10-24 x 1 10-24 x 1-1/4 10-24 x 1-1/2 10-24 x 2 1/4-14 x 1-7/8	3	Recommended Drive Speed 2250 RPM. Attaches plywood to metal. 0.035 - 0.100 #8 diameter 0.035 - 0.176 #310 diameter	


### Wafer HD w/Wings (Reamer)

Size	Point	Recommendations	Picture (Not to a particular size)
10-24 x 1-7/16	3	Attaches plywood to metal studs.	

### Modified Truss HD

Size	Point	Recommendations	Picture (Not to a particular size)
8-18 x 1/2 8-18 x 3/4 8-18 x 1 8-18 x 1-1/4 8-18 x 1-5/8 8-18 x 1-7/8 8-18 x 2-1/2 8-18 x 3 10-16 x 3/4	2-3	Attaches wire lath to metal studs. 14 - 20 gauge. Also used in metal to metal applications.	


### 410 Stainless Steel Modified Truss HD

Size	Point	Recommendations	Picture (Not to a particular size)
8-18 x 1/2	2	Attaches wire lath to metal studs. 14 - 20 gauge. Also used in metal to metal applications.	


Knoxville Bolt and Screw, Inc.  
 Phone 865-573-1991  
 Fax 865-573-8617

[www.knoxvillebolt.com](http://www.knoxvillebolt.com)  
 800-231-3309  
 800-231-9566


### Oval HD

Size	Point	Recommendations	Picture (Not to a particular size)
8-18 x 3/4 8-18 x 1 8-18 x 1-1/4 8-18 x 1/2	2	Recommended Drive Speed 2500 RPM. For countersunk holes. Aluminum to steel or steel to steel. 0.035 - 0.100	



### Oval HD SEMS w/Finishing Washer

Size	Point	Recommendations	Picture (Not to a particular size)
8-18 x 3/4 8-18 x 1 8-18 x 1-1/4	2	Attaches carpet or vinyl to 14 gauge or thinner.	

### Pancake HD

Size	Point	Recommendations	Picture (Not to a particular size)
10-16 x 5/8 10-16 x 1 10-12 x 1	3-A	Low profile head attaches panel clip to steel studs. For framing steel studs to steel. Type A for wood studs.	


### Bugle HD Drywall

Size	Point	Recommendations	Picture (Not to a particular size)
6-20 x 1 6-20 x 1-1/8 6-20 x 1-1/4 6-20 x 1-5/8 6-20 x 1-7/8	2	Attaches Gypsum board, Insulation board, or wood to metal studs. 14 - 20 gauge.	
8-18 x 2-3/8 8-18 x 2-5/8 8-18 x 3 10-16 x 3-1/2 10-16 x 4	2	Attaches double, multi, or laminated drywall to metal studs. 14 - 20 gauge.	

Knoxville Bolt and Screw, Inc.  
Phone 865-573-1991  
Fax 865-573-8617

[www.knoxvillebolt.com](http://www.knoxvillebolt.com)  
800-231-3309  
800-231-9566

### Trim HD

Size	Point	Recommendations	Picture (Not to a particular size)
6-20 x 1-5/8 6-20 x 2-1/4	2	Attaches wood trim to single or double layer of drywall to metal studs.	

Knoxville Bolt  
& Screw, Inc